

MASTERColour CDM MW Eco

MASTERColour MW eco MASTERColour CDM-T MW eco 230W/842 E40

Ceramic metal halide lamps with clear tubular or coated ellipsoid outer bulb, tailor-made to replace and outperform quartz metal halide lamps on existing gear.

Warnings and Safety

- For use with control gear designed for high pressure mercury or high-pressure sodium lamps with external ignitor
- A lamp breaking is extremely unlikely to have an impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Warm restart time can be up to 15 minutes; T15 ignitors therefore advised.

Product data

General information	
Cap-Base	E40 [E40]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 5% Failures (Nom)	12000 h
Life To 10% Failures (Nom)	16000 h
Life to 20% Failures (Nom)	20000 h
Life to 50% Failures (Nom)	30000 h
System Description	Universal
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	98 %
LSF 12000 h Rated	95 %
LSF 16000 h Rated	90 %
LSF 20000 h Rated	80 %
LSF 24000 h Rated	70 %
LSF 28000 h Rated	56 %
LSF 30000 h Rated	50 %
Flux measurement reference	Sphere

Light technical	
Color Code	842 [CCT of 4200K]
Luminous Flux (Nom)	21400 lm
Luminous Flux (Rated) (Nom)	21400 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.371
Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4200 K

MASTERColour CDM MW Eco

Luminous Efficacy (rated) (Nom)	94 lm/W
Color Rendering Index (Nom)	88
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	84 %
LLMF 8000 h Rated	82 %
LLMF 12000 h Rated	80 %
LLMF 16000 h Rated	77 %
LLMF 20000 h Rated	75 %
Ratio Scotopic/Photopic Lumens	1.87

Operating and electrical

Power (Nom)	227.0 W
Lamp Current Run-Up (Max)	2.2 A
Lamp Current (EM) (Nom)	0.212 A
Ignition Supply Voltage (Max)	198 V
Ignition Peak Voltage (Max)	5000 V
Ignition Peak Voltage (Min)	750 V
Re-Ignition Time (Min) (Max)	900 s
Ignition Time (Max)	30 s
Voltage (Max)	132 V
Voltage (Min)	118 V
Voltage (Nom)	127 V

Controls and dimming

Dimmable	No
Run-Up Time 90% (Max)	3 min

Mechanical and housing

Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	T46 [T 46mm]

Approval and application

Energy Efficiency Class	F
Mercury (Hg) Content (Max)	32 mg
Mercury (Hg) Content (Nom)	32.0 mg
Energy Consumption kWh/1000 h	227 kWh
EPREL Registration Number	473314

UV

Pet (Niosh) (Nom)	8 h/500lx


Luminaire design requirements

Bulb Temperature (Max)	550 °C
Cap-Base Temperature (Max)	250 °C

Product data

Full product code	871869659681400
Order product name	MASTERColour MW eco MASTERColour CDM-T MW eco 230W/842 E40
EAN/UPC - Product	8718696596814
Order code	928070119230
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928070119230
Copy Net Weight (Piece)	166.000 g

Dimensional drawing




MASTERColour MW eco MASTERColour CDM-T MW eco 230W/842 E40


Product	D (max)	O	L	C (max)
MASTERColour MW eco MASTERColour CDM-T MW eco 230W/842 E40	47 mm	12.4 mm	157 mm	257 mm

MASTERColour CDM MW Eco

Photometric data




MASTERColour CDM-T MW eco 230W/842 E40




MASTERColour CDM MW eco /842

Lifetime



MASTERColour CDM MW eco /842



MASTERColour CDM MW eco /842

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.