PRODUCT DATASHEET
QTP5 1X80

QUICKTRONIC® PROFESSIONAL 5 | ECG for FL 16 mm



Areas of application

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Modernization of existing systems
- Suitable for luminaires of protection classes I and II

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Perfect lamp start for applications with motion sensors
- Automatic restart after lamp replacement
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Product features

- Supply voltage: 220…240 V
- Line voltage: 198…264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

© 2023, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

- Lifetime: up to 100,000 h (temperature at T_c = 65 °C, max. 10 % failure rate)
- Energy Efficiency Index EEI: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929

© 2023, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data


Nominal wattage	88.00 W
Nominal voltage	220…240 V
Input voltage AC	198…264 V
Input voltage DC	176…276 V
U-OUT (working voltage)	330 V
Inrush current	40 A
Mains frequency	50/60 Hz
Max. ECG no. on circuit breaker 10 A (B)	12 [1)]
Max. ECG no. on circuit breaker 16 A (B)	19 [1)]
Operating frequency	40…50 kHz

1) Type B

Light technical data

Starting time	1 s

Dimensions & Weight



Length	360.00 mm
Mounting hole spacing, length	350,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	235.5 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

© 2023, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % [1)]

1) Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	100000 h [1)]

1) At T_{case} = 65°C at T_c point / 10% failure rate

Capabilities

Dimmable	No
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Suitable for fixtures with prot. class	I / II
End of lamp life safety shutdown	EOL T.2

Certificates & Standards

Approval marks – approval	VDE / VDE-EMC / ENEC 10 / CE
Standards	Acc. to EN 61347-2-3 / Acc. to EN 60929 / Acc. to EN 55015:2006 + A1:2007 / Acc. to EN 61000-3-2 / Acc. to EN 61547
Protection class	I/II
Type of protection	IP20
Energy efficiency class	A2 BAT
EEI – Energy Label	A2 BAT

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
PDF	PRODUCT DATASHEET
PDF	Certificates

© 2023, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

	DOWNLOAD DATA
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321329059	Unpacked 1		235.50 g	
4008321329066	Shipping box 20	370 mm x 96 mm x 170 mm	4881.00 g	6.04 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2023, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.