

MASTER SON APIA Plus Xtra

MASTER SON APIA Plus Xtra 150W E40 1SL/12

High Pressure Sodium lamp with opalized outer bulb, high output and longest reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information	
Cap-Base	E40 [E40]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 5% Failures (Nom)	28000 h
Life To 10% Failures (Nom)	32000 h
Life to 20% Failures (Nom)	36500 h
Life to 50% Failures (Nom)	45000 h
System Description	External Ignitor
LSF 2000 h Rated	100 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	99 %
LSF 16000 h Rated	99 %
LSF 20000 h Rated	99 %
Flux measurement reference	Sphere

Light technical	
Color Code	- [Not Specified]
Luminous Flux (Nom)	17600 lm
Luminous Flux (Rated) (Nom)	17600 lm
Chromaticity Coordinate X (Nom)	0.535
Chromaticity Coordinate Y (Nom)	0.42
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	113.64 lm/W
Color Rendering Index (Max)	25
Color Rendering Index (Nom)	-
LLMF 2000 h Rated	99 %
LLMF 4000 h Rated	98 %
LLMF 6000 h Rated	97 %
LLMF 8000 h Rated	96 %
LLMF 12000 h Rated	96 %
LLMF 16000 h Rated	95 %
LLMF 20000 h Rated	94 %

MASTER SON APIA Plus Xtra

Ratio Scotopic/Photopic Lumens	0.55

Operating and electrical

Power (Nom)	154.0 W
Lamp Current (EM) (Nom)	0.179 A
Ignition Supply Voltage (Max)	198 V
Ignition Peak Voltage (Max)	2800 V
Re-Ignition Time (Min) (Max)	180 s
Ignition Time (Max)	5 s
Voltage (Max)	115 V
Voltage (Min)	85 V
Voltage (Nom)	97 V

Controls and dimming

Dimmable	Yes
Run-Up Time 90% (Max)	4 min

Mechanical and housing

Bulb Finish	Coated glass
Bulb Shape	BD90 [BD 90mm]

Approval and application

Energy Efficiency Class	F
Mercury (Hg) Content (Max)	15.1 mg
Mercury (Hg) Content (Nom)	15.1 mg
Energy Consumption kWh/1000 h	154 kWh
EPREL Registration Number	473384


Luminaire design requirements

Bulb Temperature (Max)	350 °C
Cap-Base Temperature (Max)	250 °C

Product data

Full product code	872790092745000
Order product name	MASTER SON APIA Plus Xtra 150W E40 1SL/12
EAN/UPC - Product	8727900927450
Order code	928150919827
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928150919827
Copy Net Weight (Piece)	0.140 kg
ILCOS Code	SE-150-H/E-E40

Dimensional drawing





MASTER SON APIA Plus Xtra 150W E40 1SL/12

Product	D (max)	C (max)
MASTER SON APIA Plus Xtra 150W E40 1SL/12	91 mm	227 mm


MASTER SON APIA Plus Xtra

Photometric data






LDLD_SON-APIA-Light distribution diagram




LDPO_SON-APIA-Spectral power distribution Colour

Lifetime



LDLE_SON-APIA_0004-Life expectancy diagram



LDLM_SON-APIA_0003-Lumen maintenance diagram

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.